



DATA SHEET 24X24 PORCELAIN PAVERS



60cm x 60cm (23.62" x 23.62")

TECHNICAL DETAILS

1.**Thickness:** 3/4" (20 mm)

2. Grip: R11 A+B+C

3. **Solar Reflectance Index:** 86-38 4. **Water Absorption:** ≤ 0.5% average

5. Breaking Strength: ≥ 291.7 lbs

6. Flexural Strength: Average \geq 5076.3 psi.

7. Resistance to Deep Abrasion: ≤ 0.0107 in³.

8. Mohs Hardness Scale: ≥ 8 .

9. Coefficient of Linear Thermal Expansion: < 7.1 x 10^-6 °F^-1

10.**Thermal Shock Resistance:** No damage after 50 cycles.

11. Frost Resistance: No damage after 100 cycles.

12. Crazing Resistance: No crazing after 1 cycle.

13. **Chemical Resistance:** Minimum class B against acids, alkalis, household chemicals, and pool salts.

14. Stain Resistance: Minimum class 3.

15. **Release of Hazardous Substances:** Lead < 0.1, Cadmium < 0.01 mg/dm²

16. **Impact Resistance:** Passes test requirements.

17. Fire Reaction: Class A1fl.

18. **Color Resistance to UV Light:** No significant change.

19. **Moisture Expansion:** ≤ 0.00394 in/ft.

FEATURES

The 24x24 Elegance pavers by NT Trading offer a perfect blend of style and durability for outdoor environments. Each paver, measuring a substantial 24 inches by 24 inches, provides a robust foundation for a variety of outdoor spaces. With a practical thickness, these pavers ensure ease of installation and a smooth, cohesive appearance.

PACKAGING DETAILS

24x24: 1 pallet = 256 sqft (64 pcs/pallet. 2 pcs/bx)





DATA SHEET 24X24 **PORCELAIN PAVERS**



60cm x 60cm (23.62" x 23.62")

AVAILABLE COLORS



LIGHT GREY



INOX



BASALTO BLACK



DARK GREY



URBAN WHITE



CARAMEL



BLUESTONE



BASALTO GREY



HONEY



TAUPE



BASALTO RED



MILK



STORM